



# PROVEN RELIABILITY JOB AFTER JOB



INTRODUCING THE NEW EXPANDED AND ENHANCED SHOCK ABSORBING LANYARD RANGE FROM PROTECTA®. A MODEL FOR EVERY USER IN EVERY APPLICATION. NOW FEATURING MODELS DESIGNED FOR USERS EXPOSED TO FALLS OVER OR AROUND EDGES.

### Edge Tested Lanyards

Daily, thousands of people working at height are exposed to falls over or around edges. Those working on electrical pylons, steel fabrications, scaffolding, flat roof structures or telecoms towers today may be using shock absorbing lanyards that are not durable enough to withstand a fall across such a structure.

Protecta®'s answer to this is our new range of lanyards, designed to offer greater security to users exposed to falls over or around edges and tested rigorously over a 0.5mm radius edge.

All edge tested products in the Protecta® range are differentiated from Protecta® standard shock absorbing lanyards and bear the Edge tested logo.



#### Pro™ Stretch



#### Sanchoc™ Kernmantle Rope



#### Sanchoc™ Webbing



#### Edge Tested Lanyards



## NEW! Edge Tested Pro™ Stretch Lanyards

- Tested over a 0.5mm Radius edge
- Enhanced protection for workers exposed to working over edges
- Two layers of tube webbing offer exceptional product life & durability
- Available with Twist Lock or Triple Lock carabineer body connector for even greater security
- Differentiated from standard Pro Stretch lanyards by orange edging to label pouch and black striped tube webbing
- Various connectors are available depending on the needs of the user ranging from standard carabiners to large opening scaffold hooks



CE EN355	↔	🔗			🔑			kg	⚠️
		🔗	🔗	🔗	🔗	🔗	🔗		
AE5220SBB/SE	2.00m	🔗	18mm	Ⓢ	🔗	18mm	Ⓢ	0.79	▪
AE5220SBK/SE	2.00m	🔗	18mm	Ⓢ	🔗	60mm	Ⓐ	1.08	▪
AE5220SYK/SE	2.00m	🔗	22mm	Ⓐ	🔗	60mm	Ⓐ	1.08	▪

## Pro™ Stretch Lanyards

- Built in energy absorber – no bulky shock pack
- Elasticated tube web reduces trip hazard & damage through abrasion
- Identification labels protected from damage or removal
- Activation indicator easily identifies a deployed lanyard



CE EN355	↔	🔗			🔑			kg
		🔗	🔗	🔗	🔗	🔗	🔗	
AE5215SAA	1.50m	🔗	17mm	Ⓢ	🔗	17mm	Ⓢ	0.63
AE5215SAE	1.50m	🔗	17mm	Ⓢ	🔗	19mm	Ⓢ	0.71
AE5215SAF	1.50m	🔗	17mm	Ⓢ	🔗	50mm	Ⓢ	0.97
AE5215SAK	1.50m	🔗	17mm	Ⓢ	🔗	60mm	Ⓐ	0.91
AE5215SEF	1.50m	🔗	19mm	Ⓢ	🔗	50mm	Ⓢ	1.05
AE52175SAF	1.75m	🔗	17mm	Ⓢ	🔗	50mm	Ⓢ	1.03
AE5220SAA	2.00m	🔗	17mm	Ⓢ	🔗	17mm	Ⓢ	0.74
AE5220SAE	2.00m	🔗	17mm	Ⓢ	🔗	19mm	Ⓢ	0.82
AE5220SAF	2.00m	🔗	17mm	Ⓢ	🔗	50mm	Ⓢ	1.09
AE5220SAK	2.00m	🔗	17mm	Ⓢ	🔗	60mm	Ⓐ	1.03
AE5220SEF	2.00m	🔗	19mm	Ⓢ	🔗	50mm	Ⓢ	1.17

## NEW! Edge Tested Sanchoc™ Kernmantle Rope Lanyards

- Tested over a 0.5mm Radius edge
- Enhanced protection for workers exposed to working over edges
- 12.5mm Kernmantle rope offers exceptional durability and product life
- Available with Twist Lock carabineer body connector for even greater security
- Differentiated from standard Sanchoc kernmantle rope lanyards by Orange colour yarn



CE EN355	↔	🔗	🔑	🔗			🔑			kg	⚠️
				🔗	🔗	🔗	🔗	🔗	🔗		
AE5220REK/SE	2.00m	▪	1	🔗	19mm	Ⓢ	🔗	60mm	Ⓐ	1.20	▪
AE5315REK/SE	1.50m	▪	2	🔗	19mm	Ⓢ	🔗	60mm	Ⓐ	1.70	▪
AE5220RBB/SE	2.00m	▪	1	🔗	18mm	Ⓢ	🔗	18mm	Ⓢ	0.90	▪
AE5220RBK/SE	2.00m	▪	1	🔗	18mm	Ⓢ	🔗	60mm	Ⓐ	1.40	▪

## Sanchoc™ Kernmantle Rope Lanyards

- 10.5mm diameter kernantle rope leg material
- Rope terminations sewn with high strength polyester thread
- Identification labels protected within transparent shock pack cover
- Wide range of designs and connector options available



CE EN355	↔	🔗	🔑	🔗			🔑			kg
				🔗	🔗	🔗	🔗	🔗	🔗	
AE522/13	1.50m	▪	1	🔗	19mm	Ⓢ	🔗	19mm	Ⓢ	0.85
AE522/15	1.50m	▪	1	🔗	19mm	Ⓢ	🔗	50mm	Ⓢ	1.13
AE522/1	1.50m	▪	1	🔗	17mm	Ⓢ	🔗	17mm	Ⓢ	0.77
AE522	2.00m	▪	1	🔗	17mm	Ⓢ	🔗	17mm	Ⓢ	0.85
AE522/3	2.00m	▪	1	🔗	19mm	Ⓢ	🔗	19mm	Ⓢ	0.88
AE522/5	2.00m	▪	1	🔗	19mm	Ⓢ	🔗	50mm	Ⓢ	1.16
AE522/6	2.00m	▪	1	🔗	17mm	Ⓢ	🔗	50mm	Ⓢ	1.10
AE525	Adj. 2.00m	▪	1	🔗	17mm	Ⓢ	🔗	17mm	Ⓢ	0.86
AE525/1	Adj. 2.00m	▪	1	🔗	17mm	Ⓢ	🔗	50mm	Ⓢ	1.22
AE5310RAK	1.00m	▪	2	🔗	17mm	Ⓢ	🔗	60mm	Ⓐ	1.60
AE532/31	1.30m	▪	2	🔗	19mm	Ⓢ	🔗	50mm	Ⓢ	1.75
AE532/2	1.50m	▪	2	🔗			🔗			0.53
AE532/1	1.80m	▪	2	🔗	17mm	Ⓢ	🔗	50mm	Ⓢ	1.75
AE532/3	1.80m	▪	2	🔗	19mm	Ⓢ	🔗	50mm	Ⓢ	1.73



## Sanchoc™ Webbing Lanyards

- Supple & flexible webbing offers great ease of use
- Highly abrasion resistant webbing with 25mm & 45mm width options
- Terminations sewn with high strength polyester thread
- Identification labels protected within transparent shock pack cover
- Wide range of designs and connector options available

CE EN355	↔	🔗	👤↔	👤	🔗		🔗		👤	👤	👤	👤	👤	👤	kg
					🔗	🔗	🔗	🔗							
AE5220WAA	2.00m		25mm	1	🔗	17mm	🔗	🔗	17mm	🔗	🔗	🔗	🔗	🔗	0.76
AE5220WAE	2.00m		25mm	1	🔗	17mm	🔗	🔗	19mm	🔗	🔗	🔗	🔗	🔗	0.81
AE5220WAF	2.00m		25mm	1	🔗	17mm	🔗	🔗	50mm	🔗	🔗	🔗	🔗	🔗	1.10
AE529/1	1.50m		45mm	1	🔗	17mm	🔗	🔗	17mm	🔗	🔗	🔗	🔗	🔗	0.73
AE529/61	1.50m		45mm	1	🔗	17mm	🔗	🔗	50mm	🔗	🔗	🔗	🔗	🔗	1.00
AE529	2.00m		45mm	1	🔗	17mm	🔗	🔗	17mm	🔗	🔗	🔗	🔗	🔗	0.77
AE529/6	2.00m		45mm	1	🔗	17mm	🔗	🔗	50mm	🔗	🔗	🔗	🔗	🔗	1.75
AE5315WAA	1.50m	■	25mm	2	🔗	17mm	🔗	🔗	17mm	🔗	🔗	🔗	🔗	🔗	0.98
AE5315WAF	1.50m	■	25mm	2	🔗	17mm	🔗	🔗	50mm	🔗	🔗	🔗	🔗	🔗	1.70
AE5320WAA	2.00m	■	25mm	2	🔗	17mm	🔗	🔗	17mm	🔗	🔗	🔗	🔗	🔗	0.98
AE5320WAE	2.00m	■	25mm	2	🔗	17mm	🔗	🔗	19mm	🔗	🔗	🔗	🔗	🔗	1.17
AE5320WAF	2.00m	■	25mm	2	🔗	17mm	🔗	🔗	50mm	🔗	🔗	🔗	🔗	🔗	1.80

## Lanyard Icon Key

We have created a number of icons in order to easily communicate the features and benefits of the products. Please see the key below for further details.

### General



Dimension



Diameter



Kilogrammes



Certification

### Type



Material: Aluminium



Material: Steel

### Lanyards



Lanyard



Twin Leg



Carabiner



Screw Carabiner



Twist Lock



Triple Lock



Connector:  
Lanyard End



Connector:  
User End



Scaffold Hook



Snap Hook

## GLOBAL LEADER IN FALL PROTECTION

### Capital Safety is the Global leader in fall protection equipment, systems and anchors.

Capital Safety est le leader mondial en matière d'équipement, de systèmes et d'ancrages de protections antichute.

Capital Safety ist weltweit führend auf dem Gebiet von Absturzsicherungs-ausrüstung, -systemen und Anschlagmöglichkeiten.

Capital Safety es el líder mundial en equipos, sistemas y anclajes de protección contra caídas.

Capital Safety is wereldleider in valbeveiligingsapparatuur, -systemen en verankeringen.

Capital Safety è leader globale nell'anticaduta per dispositivi di protezione individuale, sistemi e ancoraggi.

Capital Safety är globala inom utrustning, system och förankringar för fallskydd.

### EUROPE, MIDDLE EAST & AFRICA

#### FRANCE

Le broc Center, Z.I. 1re Avenue – BP15  
06511 Carros Le Broc Cedex, FRANCE  
t: +33 (0) 4 97 10 00 10  
f: +33 (0) 4 93 08 79 70

#### UK

5a Merse Road, North Moons Moat  
Redditch, B98 9HL, UK  
t: +44 (0) 1527 548 000  
f: +44 (0) 1527 591 000

#### GERMANY

Hagener Strasse 44, D-57489,  
Drolshagen, GERMANY  
t: +49 (0) 2 76 18 33 82 29  
f: +40 (0) 2 76 18 33 81 93

#### DUBAI

ME Branch Office, PO Box 17769  
JAZFA, DUBAI – UAE  
t: +971 (4) 88 11 4 66  
f: +971 (4) 88 11 4 67

### CUSTOMER SERVICES

 00 800 999 55500

 [information@capitalsafety.com](mailto:information@capitalsafety.com)

 [capitalsafety.com](http://capitalsafety.com)



All rights reserved. The material contained herein is copyrighted; no part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise without prior written permission from Capital Safety.

Ref: 9700823