DBI-SALA<sup>®</sup> NANO-LOK™ FOR HOT WORK USE

THE FIRST EVER SELF RETRACTING LIFELINE DESIGNED FOR WELDING, GRINDING AND HIGH HEAT APPLICATIONS

### DURABLE

Reinforced webbing with Nomex®/Kevlar® fiber to with stand sparks, weld splatter and other high heat exposure.

### VERSATILE

5 different Nano-Lok® configurations, single and twin-leg, that can be connected at foot level to meet your specific needs.

### SAFE

Arc flashed to 8 calories (8cal/cm2), for hot work use in applications like welding, grinding and torching. Meets or exceeds industry standards. CE EN360:2002.





JII.

VANO-LOP

### THE ULTIMATE IN FALL PROTECTION

### DBI-SALA<sup>®</sup> NANO-LOK<sup>™</sup> FOR HOT WORK USE

## **NANO-LOK<sup>™</sup> FOR HOT WORK USE FEATURES**





Single-Leg Alum. Snap Rebar hook 57 mm opening 1.5 kg – 2 m

# **REF: 3101523**

### Single-Leg

Steel Snap hook 19 mm opening 1.6 kg – 2 m

### REF: 3101524

Twin-Leg Steel Snap Rebar hook 63 mm opening 3.1 kg – 2 m



### **REF: 3101525**

Twin-Leg Alum. Snap Rebar hook 57 mm opening 3.2 kg – 2 m

### **SPECIFICATIONS:**

Reinforced webbing with Nomex® / Kevlar® fiber\*. Resist to sparks and weld splatters. Arc-flashed resistant to 8 cal / cm2 Certification: CE EN360 : 2002

Capacity: 140 kg Connection level: Can be connected at foot level Length = 2 m

\*DuPont<sup>TM</sup>, Kevlar<sup>®</sup>, and Nomex<sup>®</sup> are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.





### CAPITAL SAFETY GROUP, EMEA

t: +33 (0) 4 97 10 00 10 f: +33 (0) 4 93 08 79 70

### 00 800 999 55500

t: +44 (0) 1527 548 000 f: +44 (0) 1527 591 000 information@capitalsafety.com

Capitalsafety.com

All rights reserved. The material contained herein is copyrighted; no part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise without prior written permission from Capital Safety.

Ref: 9701360